

6455-C

FROZEN BEVERAGE FREEZER

Two flavor, Countertop, Gravity feed



CE

Most Compact & Versatile

Two flavor countertop model for frozen beverage and smoothies

Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

Simple Control, Easy Operation

Simple and intuitive control system makes operation and viscosity adjustment easy, swift and more precise

Low Mix Indicator

Light turns "ON" at low mix to alert operator to add mix

See-through Dispensing Door

Clear dispensing door design makes product more attractive and serves as great marketing tool

Standby & Indicator

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight; Indicator light turns ON blue under Standby mode

Perfect solution for alcoholic and non-alcoholic

frozen beverages in bars, restaurants, hospitals,

schools and kiosks

SPACEMAN INTERNATIONAL (HK) CO. LTD.

FACTORY: 1 GUANZE RD, INDUSTRY PARK, DAIXI TOWN, HUZHOU, ZHEJIANG, CHINA 313023

Hopper Agitators

Maintain product consistency and prevent product separation

Intertek

Self-closing Dispensing Valves

Automatically prevents product overflow after dispense

Safety Protections

- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating

Light Box (Optional)

- Illuminates flavor cards to attract more business
- Changes color to indicate Low Mix and Standby

One-hand Operated Spinner (Optional)

- Adds ability to blend and offer more variaties of treats
- Allows for multi-tasking one-hand operation that helps increase productivity and reduce serving time



PHONE: +86 572 3826788 FAX: +86 572 3826755 Email: info@spaceman-company.com www.spaceman-company.com






6455-C

FROZEN BEVERAGE FREEZER

46.4



SPECIFICATIONS	
Flavors	
Freezina Cylinde	ers

Freezing Cylinders	2 x 3.8L / 4.0qt
Mix Hoppers	2 x 8.0L / 8.5qt
Output Capacity (250ml)	112 serves/hr
Clearance Requirements	152mm/6" on back

2

Weight	Kg/lb	
Net	146 / 325	
Shipping	166 / 369	
Volume	0.48 CBM / 17.10 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	476 / 18.7	520/20.5
Depth	651/25.6	853/33.6
Height	950 / 37.4	1090 / 42.9

Electrical	MFS	MCA	Power(kW)
220-240/50/1	15	13	2.0
220-240/60/1	15	13	2.1
110-115/60/1	20	16	1.6

(1.83) (29.76) С C 368.9 (14.52) สา DRIP TRAY(FAR SIDE) 504.5 (19.86) 446 (17.56) 150 (5.91) 0 484 651 (19.06) (25.63)

756

FEATURES	
Control Systems	Two, Mechanical
Refrigerated Hoppers	
Hopper Agitators	
Standby Mode	
Auto Closing Dispensing Valves	
Low Mix Indicator Light	
Low Mix Indicator Alarm	
Standby Mode	
Standby Indicator Light	
High Pressure Protection	
Thermal Overload Protection	

AVAILABLE OPTIONS	
Top Air Discharge Chute	
Spinner	
Light Box	\checkmark

 $\boldsymbol{\cdot}$ Above specifications are subject to change without notice

SPACEMAN USA

224 Commerce St. Unit A1, Broomfield, CO 80020 PHONE: +01 720-328-1020 FAX: +01 720-528-8113 Email: sales@spacemanusa.com www.spacemanusa.com